

**HYDRAULIC SERIES ADVANTAGE**



For tough winching applications, no product performs better than Superwinch hydraulic winches.

- The Superwinch line of hydraulic winches provides you with a continuous duty solution to your winching requirements.
- Designed with the toughest commercial/industrial applications in mind.
- Available in a full range of planetary and worm gear drives with capacities from 8,000 to 30,000 pounds.
- Many of our hydraulic winches are rated in accordance to SAE J 706 standards and are CE certified.
- Engineered to ensure total reliability.
- Most models are available with manual or pneumatic free spool, load holding brakes, and LCV to give you precise control of your load.

## H8P

**Part Number:**

H8P: **5050A**

**Specifications**

- Rated Line Pull: 8,000 lbs (3,630 kg)
- Motor: High torque
- Gearing: 2-Stage Planetary Differential
- Gear Ratio: 16:1
- Maximum Oil Pressure: 1,800 psi (124.13 BAR) 126.58 kg/cm<sup>2</sup>
- Maximum Oil Flow: 15 gpm (57 l/min)
- Freespooling Clutch: Manual Release Lever Pneumatic P/N 5603
- Short Drum: 23" L x 8.25" D x 9.0" H (584.2mm L x 209.5mm D x 228.6mm H)
- Recommended Wire Rope: 3/8" (9.5mm) x 75' (23m)
- Long Drum: 25.5" L x 8.25" D x 9.0" H (647.7L x 209.5D x 228.6H)
- Recommended Wire Rope: 3/8" (9.5mm) x 100' (30m) long drum
- Drum Diameter: 3.5" (90mm)
- Drum Length: Short Drum 7.5" (190mm)
- Drum Length: Long Drum 10" (254mm)
- Roller Fairlead: Optional P/N 5600 (short drum) /5610A (long drum)
- Mounting Bolt Patten: Side, Foot, Angle, Flatbed, or Low Mount
- Installed Weight: 84 lbs (38 kg) without wire rope
- Shipping Weight: 92 lbs (41.73 kg) without wire rope
- Limited One Year Warranty

**Performance** (First layer on drum)

Line Speed FPM (MPM) 40 (13.8)

## H10P

**Part Number:**

H10P: **5170A**

**Specifications**

- Rated Line Pull: 10,000 lbs (4,540 kg)
- Motor: High torque
- Gearing: 2-Stage Planetary Differential
- Gear Ratio: 16:1
- Maximum Oil Pressure: 1,700 psi (117.24 BAR) 119.55 kg/cm<sup>2</sup>
- Maximum Oil Flow: 15 gpm (57 l/min)
- Freespooling Clutch: Spring engaged/Optional Pneumatic P/N 5603
- Short Drum: 23" L x 8.25" D x 9.0" H (584.2L x 209.5D x 228.6H)
- Recommended Wire Rope: 7/16" (11mm) x 75' (23m)
- Long Drum: 25.5" L x 8.25" D x 9.0" H (647.7mm L x 209.5mm D x 228.6mm H)
- Wire Rope: 7/16" (11mm) x 100' (30m) long drum
- Drum Diameter: 3.5" (90mm)
- Drum Length: Short Drum 7.5" (190mm)
- Drum Length: Long Drum 10" (254mm)
- Roller Fairlead: Optional P/N 5600 (short drum) / 5610A (long drum)
- Mounting Bolt Patten: Side, Foot, Angle, Flatbed, or Low Mount
- Installed Weight: 84 lbs (38 kg) without wire rope
- Shipping Weight: 92 lbs (41.73 kg) without wire rope
- Limited One Year Warranty

**Performance** (First layer on drum)

Line Speed FPM (MPM) 30 (9.4)

